

# I Damaschi



Ver. 1



## Technical Data Sheet

### Elegant “Damasco” effect, interior decorative finish

An extremely elegant, old-classical, damask effect, wall decoration. The glaze finishing can be Transparent, enhancing the tone of the base coat, or in the dazzling Silver, Gold or Copper metallic versions. When applied over a colored, matt latex paint, the effect achieved will recall fine adornments of the past. Ideal for the do-it-yourself market, it is simply dabbed on to add opulent shimmer, creating a unique and innovative look to your walls with the greatest of ease. I DAMASCHI Transparent can also be used mixed 1:1 with METALTOP KS to create a splendid gold enamel effect finish.



#### INTENDED USE

Any normal, paintable interior wall surface, either Gypsum plaster based or rendered masonry.



#### SURFACE TREATMENT

The substrate must be smooth, uniform, clean, dry and free from peeling paint. In case of old and powdery walls or in presence of weak paint, apply a coat of ADIFIX primer thinned as specified and allow to dry.

Apply one or two base coats of a prime quality, washable, matt paint in the color of your choice. ADIDROL B' is the type we advise to use.



#### COLOR

The product is ready to use and available either in Transparent or in the stylish Silver, Gold or Copper versions.



#### APPLICATION

Dip the sponge, chamois pad or rag stippler into a small quantity of the chosen DAMASCHI finish, avoiding excess product, and apply directly to the painted wall by dabbing on lightly. Apply randomly, rotating the contact point of the tool to the wall and without excessively overlapping the design to allow the matt effect of the base to show through.



#### THINNING

Ready to use.



#### AVERAGE SPREAD RATE

Spread rate (per coat): 15 to 20 m<sup>2</sup>/litre



#### DRYING TIME AT 25° C

2 to 3 hours, touch dry



#### SPECIFIC GRAVITY

1010 ± 20 g/l



#### VISCOSITY

(Brookfield 20°C): 2500 to 3500 mPa.s



#### V.O.C. (Directive 2004/42/CE)

Cat. L BA - Direttive 2004/42/CE - Val Max.: 200 g/l - Val Eff.: 65 g/l

Any information supplied whether verbal or in writing, is for guidance only as conditions and feasibility of use may be influenced by external factors beyond our control and is therefore given in good faith but without warranty. Adicolor reserves the right to modify any data and information without notice. Our technical service is available for any further detailed information.

