

joyé



Ver. 1



Technical Data Sheet

Joyé: Glitters of light

Our ambition is to create an effect that will surprise and astonish. Adicolor has once again succeeded in producing a truly spectacular decorative finish that will add the feeling of outstanding luxury and elegance to any interior. It can be used to enhance a feature wall, or to adorn columns, doors or even parts of furniture. An easy, roller applied finish, composed of a basecoat of FONDO UNIVERSALE, and the impressive and sparkling JOYÉ proposed in a choice of 16 charming colors.



INTENDED USE

Any well treated, smooth, interior wall surface



SURFACE TREATMENT

Ensure that the surface is clean, dry and sound. In case of new plasters, old and powdery walls, apply a coat of ADIFIX primer thinned as specified and allow to dry. Using a short-pile roller, apply one or two basecoats of FONDO UNIVERSALE colored with the specified quantity of TINTER as indicated in the catalogue.



COLOR

JOYÉ is supplied in two bases: Silver and Gold that can each be colored by adding the specified quantity of Adicolor TINTER as indicated on the catalogue.



APPLICATION

Once the basecoat is well dry, proceed with the application of JOYÉ colored to the selected tone. Pour the finish into a paint tray and load a short pile roller well, running it on the tray several times to ensure it is well saturated. Roll the product to the wall in short, crossed and irregular strokes. Reload the roller frequently and be sure you always have ABUNDANCE of paint while rolling, being careful not to make excess over-rolls and run low of product. In this way you will have a well spread finish of uniform appearance with some shadowed effects that are typical of this effect.



THINNING

Ready to use or with max. 5% water



AVERAGE SPREAD RATE

Spread rate (per coat): 7 to 8 m²/litre



DRYING TIME AT 25° C

About 4 to 6 hours



SPECIFIC GRAVITY

GOLD: 1090 +/- 20 g/l - SILVER: 1120 +/- 20 g/l



VISCOSITY

(Brookfield à 20°C): 2100 to 2500 mPa.s



V.O.C. (Directive 2004/42/CE)

Cat. L BA - Direttive 2004/42/CE - Val Max.: 200 g/l - Val Eff.: 38 g/l

Any information supplied whether verbal or in writing, is for guidance only as conditions and feasibility of use may be influenced by external factors beyond our control and is therefore given in good faith but without warranty. Adicolor reserves the right to modify any data and information without notice. Our technical service is available for any further detailed information.

